Technical datasheet

Fabric EZP 12/1 0+0 white 400CFM HR

Ammeraal Beltech
Innovation & Service in Belting

Article code: ZLFA583091

General information	
Product group	Ziplink
Industry segment	Wood
Main product feature	Hydrolysis resistant, Heat resistant
Indication of use	Flat, Rollers, Slider bed

Belt construction		
Tension layer		Ziplink fabric, flexible
Number of plies		1
Top side	material	fabric, polyester
	finish	bare fabric
	color	white
Bottom side	material	fabric, polyester
	finish	bare fabric
	color	white

Characteristics	
Food Grade (FG)	no
Antistatic (AS)	no
Flame-retardant (FR)	no
ATEX approval	no

Technical data						
Force at 1% elongation	ISO 21181		12	N/mm	68.52	lbs/in.
Thickness	AB method KV.002		2.3	mm	0.09	in.
Weight	AB method KV.004		1.62	kg/m²	0.33	lbs/ft²
Operating temperature	continuous	from / to	-10 / 180	°C	14 / 356	°F
	short	from / to	-10 / 180	°C	14 / 356	°F
Minimum pulley diameter	flexing		12	mm	0.47	in.
	backflexing		12	mm	0.47	in.
Manufacturing width	standard		4000	mm	157.48	in.
	maximum		4000	mm	157.48	in.

Fabrication

Ziplink belts can be endlessed, very easy and quick splicing without presses, fasteners or glues. Refer to the technical information for more information about splicing of Ziplink belts.

Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

We recommend to keep the belt tension to a practical working minimum to maximize the service life of the belt and machine parts.

Always protect belts from sunlight/UV-radiation, avoid temperatures below 10°C and above 40°C, dust and dirt. Store belts in a cool and dry place and if possible in their original packaging.

For details consult 'Storage and handling instructions' or contact our specialist.

Because of continuous development, the presented data is subject to alteration. This da above stated information. Subject to the general terms and conditions of sale and delive	ta replaces that included in previous publery, as applied by its operating companies	ications. Ammeraal Beltech excludes any lia s, are all activities performed and services r	bility for the incorrect use of the endered by Ammeraal Beltech.