Technical datasheet

Nonex ESF 3/1 0+A8 light blue FG

Article code: SBNO581913



General information			
Product group	Synthetic Belts		
Main product feature	Foodgrade, Oil & grease resistant		

Belt construction		
Number of plies		1
Top side	material	Nonex, PVC
	color	Light blue
Bottom side	material	fabric
	finish	bare fabric
	color	natural

Characteristics					
Food Grade (FG)	yes	EC 1935/2004, EU 10/2011; FDA			
Antistatic (AS)	no				
High conductive (HC)	no				
Flame-retardant (FR)	no				
ATEX approval	no				

Technical data						
Thickness	AB method KV.002	total	1.85	mm	0.07	in.
		top cover	unknown	mm		in.
Weight	AB method KV.004		0	kg/m²	0	lbs/ft²
	maximum		10000	mm	393.7	in.

Fabrication

Hot splicing is always preferable. Glueing can only be done when the belt is exposed to normal temperature and the humidity is not excessive. For the working method, consult the splice information and the equipment literature. Apply the recommended splice as indicated in the seperate information.

Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

We recommend to keep the belt tension to a practical working minimum to maximize the service life of the belt and machine parts.

Always protect belts from sunlight/UV-radiation, avoid temperatures below 10°C and above 40°C, dust and dirt. Store belts in a cool and dry place and if possible in their original packaging.

For details consult 'Storage and handling instructions' or contact our specialist.