

PTFE KEV Mesh K76-250 4x4

Article code: PPFK000002

General information

Product group	Peak Products
----------------------	---------------

Belt construction

Fabric tension layer	aramid
-----------------------------	--------

Color	Straw
--------------	-------

Characteristics

Food Grade (FG)	yes	Yes; Yes; Yes
------------------------	-----	---------------

Antistatic (AS)	no	
------------------------	----	--

Technical data

Belt thickness			0.76 mm	0.03 in.
Weight			0.25 kg/m ²	0.05 lbs/ft ²
PTFE content			40 %	
Operating temperature	continuous	from / to	-73 / 260 °C	-99.4 / 500 °F
	short	from / to	-73 / 300 °C	-99.4 / 572 °F
Manufacturing length	maximum		100000 mm	3937.01 in.
Manufacturing width	standard		2600 mm	102.36 in.
	maximum		5000 mm	196.85 in.

Fabrication

Recommended splice method	Peak Products
----------------------------------	---------------

Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

Keep the belt tension to a practical working minimum for maximum belt and machine life.

Store loose and wrapped in plastic. The allowable product temperature may vary.

Consult our specialists in case of questions or remarks.