Technical datasheet

AmSqueeze 515 A18-A18 2430x220x15mm



Article code: EWMS000192

General information				
Product group	endless woven			
Industry segment	Food: Meat & poultry			
Main product feature	Foodgrade, Abrasion resistant, Oil & grease resistant, Cut resistant			
Application	Soft Separator			
Indication of use	Special fine structured surface, Abrasive applications			

Belt construction				
Tension layer	polyester			
Number of plies		1		
Top side	material	rial Ropanyl, TPU		
	finish	profile, A18 Fine square profile		
	color	white		
Bottom side	material	rial Ropanyl, TPU		
	finish	profile, A18 Fine square profile		
	color	white		

Characteristics					
Food Grade (FG)	yes	EC 1935/2004, EU 10-2011; FDA			
Antistatic (AS)	no				
Flame-retardant (FR)	no				

Technical data						
Hardness	ISO 868	top side	85A	Shore		
		bottom side	85A	Shore		
Force at 1% elongation	ISO 21181		28	N/mm	159.88	lbs/in.
Thickness		total	15	mm	0.59	in.
		top cover	6.2	mm	0.24	in.
		bottom cover	6.2	mm	0.24	in.
Weight			24.4	kg/m²	5	lbs/ft²
Length		from / to	2430	mm		in.
Width		from / to	220	mm		in.
Operating temperature	continuous	from / to	-20 / 90	°C	-4 / 194	°F
	short	from / to	-30 / 110	°C	-22 / 230	°F
Minimum pulley diameter			150	mm	5.91	in.

Tolerances				
Length	± 1 %	minimum ±	20 mm	0.79 in.
Width		from / to	-1 / +1 mm	-0.04 / +0.04 in.
Thickness		±	0.2 mm	0.01 in.

Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

Because of continuous development, the presented data is subject to alteration. This data replaces that included in previous publications. Ammeraal Beltech excludes any liability for the incorrect use of the above stated information. Subject to the general terms and conditions of sale and delivery, as applied by its operating companies, are all activities performed and services rendered by Ammeraal Beltech.