

# Solicord Round TPU 85A Ultramarine Blue RO FG 50

Article code: SCRB000429

## General information

Product group	SoliCord
---------------	----------

## Construction

Material	TPU
(Top)surface finish	Roughened
Color	ultra marine blue
Shape	Round
Execution	solid

## Characteristics

Food Grade (FG)	yes	all foodstuff; all foodstuff
Antistatic (AS)	no	
ATEX approval	no	

## Technical data

Hardness	ISO 868		88A Shore	
Recommended pre-tension			4-8 %	
Working tension			18 daN/cm <sup>2</sup>	
Diameter			5 mm	0.2 in.
Cross section			0.197 cm <sup>2</sup>	
Weight			0.024 kg/m	0 lb/ft
Operating temperature	continuous	from / to	-30 / 80 °C	-22 / 176 °F
Minimum pulley diameter			50 mm	1.97 in.
Coefficient of friction	against steel	dynamic	0,45	
	against PE		0,3	
	against HDPE		0,25	
Manufacturing length	maximum		50000 mm	1968.5 in.

## Fabrication

Recommended splice types	Butt weld
Splice equipment	Only use equipment supplied or approved by Ammeraal Beltech.
Splicing on site	Always first make a test splice to confirm the right settings and proper pre-heating of the equipment.

## Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ. Keep the belt tension to a practical working minimum for maximum belt and machine life. Always protect belts from sunlight/UV-radiation, avoid temperatures below 10°C and above 40°C, dust and dirt.