

# Soliflex TPU/50 M1T light blue FG

Article code: SFPU000946

## General information

<b>Product group</b>	Soliflex
----------------------	----------

## Belt construction

<b>Material</b>	TPU
<b>Top side</b>	M1 Fine matt finish, M1 Fine matt finish
<b>Bottom side</b>	M1 Fine matt finish, M1 Fine matt finish
<b>Color</b>	Light blue

## Characteristics

<b>Food Grade (FG)</b>	yes	EU 1935/2004, EU 10/2011; FDA; USDA
------------------------	-----	-------------------------------------

## Technical data

<b>Hardness</b>	ISO 868		53D Shore	
<b>Force at 1% elongation</b>	ISO 21181		4 N/mm	22.84 lbs/in.
<b>Belt thickness</b>			5 mm	0.2 in.
<b>Weight</b>			6.3 kg/m <sup>2</sup>	1.29 lbs/ft <sup>2</sup>
<b>Operating temperature</b>	continuous	from / to	-5 / 70 °C	23 / 158 °F
<b>Minimum pulley diameter</b>	flexing		160 mm	6.3 in.
	backflexing		160 mm	6.3 in.
<b>Manufacturing width</b>	maximum		1376.1 mm	54.18 in.
	standard		1371.6 mm	54 in.

## Fabrication

<b>Recommended splice method</b>	Butt weld
----------------------------------	-----------

## Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.  
 Keep the belt tension to a practical working minimum for maximum belt and machine life.  
 Store loose and wrapped in plastic. The allowable product temperature may vary.