**Technical datasheet** 

## Flexam EZP 10/1 0+A20 black FR

Article code: ZLFL583050



General information	
Product group	ZipLink
Main product feature	Flame retardant, Non logo
Indication of use	Slider bed, Rollers, Flat, Troughed

Belt construction				
Tension layer		Ziplink fabric, flexible		
Number of plies		1		
Top side	material	Flexam, PVC		
	finish	profile, A20 Diamond profile 65 mm		
	color	black		
Bottom side	material	Mesh, polyester		
	finish	bare fabric		
	color	white		

## Characteristics yes

Technical data						
Hardness	ISO 868	top side	65A	Shore		
Force at 1% elongation	ISO 21181		10	N/mm	57.1	lbs/in.
Thickness	AB method KV.002		8.4	mm	0.33	in.
Weight	AB method KV.004		7.2	kg/m²	1.47	lbs/ft²
Operating temperature	continuous	from / to	-15 / 80	°C	5 / 176	°F
	short	from / to	-15 / 100	°C	5 / 212	°F
Manufacturing width	standard		2000	mm	78.74	in.
	maximum		2020	mm	79.53	in.

## **Fabrication**

Ziplink belts can be endlessed, very easy and quick splicing without presses, fasteners or glues. Refer to the technical information for more information about splicing of Ziplink belts.

## **Additional information**

Flame-retardant (FR)

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

We recommend to keep the belt tension to a practical working minimum to maximize the service life of the belt and machine parts.

Always protect belts from sunlight/UV-radiation, avoid temperatures below 10°C and above 40°C, dust and dirt. Store belts in a cool and dry place and if possible in their original packaging.

For details consult 'Storage and handling instructions' or contact our specialist.

Because of continuous development, the presented data is subject to alteration. This data above stated information. Subject to the general terms and conditions of sale and delivery	replaces that included in previous publication y, as applied by its operating companies, are	ns. Ammeraal Beltech excludes any liability all activities performed and services render	for the incorrect use of the ed by Ammeraal Beltech.