Endless Woven K8486BP AmDough Cotton 2.8mm



Article code: RMFA000096

Article code: RMFA000096								
General information								
Product group	endless woven	endless woven						
Industry segment	Food: Bakery	Food: Bakery						
Main product feature	Foodgrade, Moist	Foodgrade, Moisture absorbant, Non-fraying						
Application	Rotary moulder b	Rotary moulder belt, Rotary cutter, Oven infeed belt						
Indication of use	Knife edge transf	Knife edge transfer, Abrasive applications						
Belt construction								
Tension layer		Twill, cotton-polyamide						
Number of plies		1						
Bottom side	material	material Ropanol, PUR						
	finish	finish impregnation						
		transparent						
Characteristics								
Food Grade (FG)	vos	EC 1025	5/2004, EU 10-2011; FDA					
roou diade (rd)	yes	LC 1933	72004, LU 10-2011, FDA					
Technical data								
Tensile Strength	ISO 21181			120	N/mm	685.22	lbs/in.	
Thickness			total	2.8	mm	0.11	in.	
Weight				1.6	kg/m²	0.33	lbs/ft²	
Length			min. / max.	800 / 52000	mm	31.5 / 2047.24	in.	
Width			min. / max.	40 / 3400	mm	1.57 / 133.86	in.	
Operating temperature	continuous		from / to	-10 / 90	°C	14 / 194	°F	
	short		from / to	-30 / 110	°C	-22 / 230	°F	
Minimum pulley diameter				5	mm	0.2	in.	
Tolerances								
Length	± 2 %		minimum ±	20	mm	0.79	in	
Width	± 2 %		minimum ±		mm	0.08		
Thickness	- 2 /0		±		mm	0.02		
· · · · · · · · · · · · · · · · · · ·			_	0.5		0.02		

Process and Conveyor	Belt

Top view



Belttype	Material	Weave	Belt Thickness [mm]
AmDough 100	cotton	broken twill	2.8
AmDough 90	cotton	broken twill	2.4
AmDough 80	cotton / polyamide	broken twill	2.4
AmDough 70	cotton	plain	2.0
AmDough 60	cotton / polyamide	broken twill	2.4
AmDough 50	cotton / polyamide	plain	1.8
AmDough 40	cotton / polyamide	plain	2.0
AmDough 20	cotton / polyester	plain	2.0

There is a linear relationship between the AmDough absorption numbers:

Heavy dough: wet, high degree of moisture, AmDough belt with higher absorption factor

Light dough: dry, low degree of moisture, AmDough belt with lower absorption factor

Top side: always uncoated

Bottom side: PUR transparent food grade impregnation for stability, better wear resistance and longer belt life

Belt edges are reinforced with polyamide selvedges.

Dimension: length up to 100 m, width up to 3400 mm

Broken twill (GK) types are also available as Twill (k) versions.

Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

Diameter of knife edge <135° [mm]
5
4
4
3
4
3
3
3