**General information** 

## Soliflex TPU/40 M1T beige FG 98A

Article code: SFPU000979



Product group	Soliflex
Main product feature	Chemical resistant, Non-stick, Wear resistant
Belt construction	
Material	TPU-E
Top side	M1 Fine matt finish, M1 Fine matt finish
Bottom side	Matt, M1 Fine matt finish
Color	beige

Characteristics		
Food Grade (FG)	yes	EU 1935/2004, EU 10/2011; FDA; USDA

Technical data						
Hardness	ISO 868		98A	Shore		
Force at 1% elongation	ISO 21181		2.7	N/mm	15.42	lbs/in.
Belt thickness			4	mm	0.16	in.
Weight			5.2	kg/m²	1.07	lbs/ft²
Operating temperature	continuous	from / to	-10 / 70	°C	14 / 158	°F
Minimum pulley diameter	flexing		na	mm		in.
	backflexing		na	mm		in.
Manufacturing width	maximum		1371.6	mm	54	in.
	standard		1371.6	mm	54	in.

Fabrication	
Recommended splice method	na

## Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ. Keep the belt tension to a practical working minimum for maximum belt and machine life.

Store loose and wrapped in plastic. The allowable product temperature may vary.