

GG N22 RFQ blue

Article code: FBGG054553

General information

Product group	High performance flat belts
Product sub type	QuickSplice
Industry segment	Paper & print; Postal automation
Main product feature	Elastic
Application	Paper processing, Printing & finishing, Mail handling
Indication of use	Bi-directional, High efficient rubber cover

Belt construction

Tension member		Thermoplastic elastomer
Top side	material	XNBR elastomer
	finish	Fine
	color	blue
Bottom / Pulley side	material	XNBR elastomer
	finish	Rough
	color	black

Characteristics

Food Grade (FG)	no	
Antistatic (AS)	yes	
High conductive (HC)	no	
ATEX approval	no	

Technical data

Belt thickness	ISO 2286-3		1.5 mm	0.06 in.
	tolerance +/-		0.1 mm	0 in.
Weight	ISO 290703-1		1.4 kg/m ²	0.29 lbs/ft ²
Force at 6% elongation	ISO 21181	dynamic	2.2 N/mm	12.56 lbs/in.
	ISO 527	static	4.25 N/mm	24.27 lbs/in.
Recommended elongation		min. / max.	2 / 6 %	
Coefficient of friction, dynamic	ISO 21182	bottom side to steel	0,6 μ	
		top side to steel	0,5 μ	
Minimum pulley diameter	flexing		15 mm	0.59 in.
	back flexing		15 mm	0.59 in.
Operating temperature	continuous	from / to	0 / 60 °C	32 / 140 °F
Belt width	standard		570 mm	22.44 in.

Fabrication

Recommended splice method	QuickSplice30
----------------------------------	---------------

Additional Information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

Consult our specialists for further instructions regarding joining, storage & maintenance, tracking & tensioning.

Consult our specialists for calculations with our E-RappCalc© technical calculation program.

Our material, as well as the packaging, must be disposed of in a professional and environmentally friendly manner.