**Technical datasheet** 

## Felt NPF 32 black AS

Article code: SBFE000032



General information	
Product group	Synthetic Belts
Industry segment	Metal; Airports; Logistics
Main product feature	Antistatic, Impact resistant
Indication of use	Slider bed, Rollers, Flat

Belt construction		
Tension layer		felt, flexible
Number of plies		1
Top side	material	felt, FE
	finish	felt
	color	black
Bottom side	material	felt, FE
	finish	felt
	color	black

Characteristics			
Food Grade (FG)	no		
Antistatic (AS)	yes	ISO 21178	
High conductive (HC)	no		
Flame-retardant (FR)	no		
ATEX approval	no		

Technical data						
Force at 1% elongation (static)	ISO 21181		10	N/mm	57.1	lbs/in.
Thickness	AB method KV.002	total	3.20	mm	0.13	in.
Weight	AB method KV.004		1.6	kg/m²	0.33	lbs/ft²
Operating temperature	continuous	from / to	-20 / 120	°C	-4 / 248	°F
	short	from / to	-20 / 120	°C	-4 / 248	°F
Minimum pulley diameter	flexing		60	mm	2.36	in.
	backflexing		60	mm	2.36	in.
Manufacturing width	standard		3200	mm	125.98	in.

## **Fabrication**

Hot splicing is always preferable. Glueing can only be done when the belt is exposed to normal temperature and the humidity is not excessive. For the working method, consult the splice information and the equipment literature. Apply the recommended splice as indicated in the seperate information.

## **Additional information**

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

We recommend to keep the belt tension to a practical working minimum to maximize the service life of the belt and machine parts.

Always protect belts from sunlight/UV-radiation, avoid temperatures below 10°C and above 40°C, dust and dirt. Store belts in a cool and dry place and if possible in their original packaging.

For details consult 'Storage and handling instructions' or contact our specialist.

Because of continuous development, the precented data is subject to alteration. This data contacts that included in activities a few continuous development.	as any liability for the incorrect use of the
Because of continuous development, the presented data is subject to alteration. This data replaces that included in previous publications. Ammeraal Beltech exclude above stated information. Subject to the general terms and conditions of sale and delivery, as applied by its operating companies, are all activities performed and se	ervices rendered by Ammeraal Beltech.