

## TG P02.05 SC

Article code: FBTG054548

### General information

<b>Product group</b>	High performance flat belts
<b>Product sub type</b>	Classic
<b>Industry segment</b>	Textile
<b>Application</b>	Spindle tape

### Belt construction

<b>Tension member</b>		Mixed fabric
<b>Top side</b>	<b>material</b>	Mixed fabric
	<b>finish</b>	smooth
	<b>color</b>	white
<b>Bottom / Pulley side</b>	<b>material</b>	NBR elastomer
	<b>finish</b>	Fabric textured
	<b>color</b>	green

### Characteristics

<b>Food Grade (FG)</b>	no
<b>Antistatic (AS)</b>	yes
<b>High conductive (HC)</b>	no
<b>ATEX approval</b>	no

### Technical data

<b>Belt thickness</b>	ISO 2286-3		0.55 mm	0.02 in.
<b>Weight</b>	ISO 290703-1		0.6 kg/m <sup>2</sup>	0.12 lbs/ft <sup>2</sup>
<b>Force at 1% elongation</b>	ISO 21181	dynamic	1.9 N/mm	10.85 lbs/in.
<b>Recommended elongation</b>		from / to	0.5 / 2 %	
<b>Coefficient of friction, dynamic</b>	ISO 21182	bottom side to steel	0,15 μ	
		top side to steel	0,5 μ	
<b>Minimum pulley diameter</b>	flexing		10 mm	0.39 in.
	back flexing		10 mm	0.39 in.
<b>Operating temperature</b>	continuous	from / to	0 / 80 °C	32 / 176 °F
<b>Belt width</b>	standard		600 mm	23.62 in.

### Fabrication

<b>Recommended splice method</b>	WedgeSkive75D-0.5-1.4
----------------------------------	-----------------------

### Additional Information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

Consult our specialists for further instructions regarding joining, storage & maintenance, tracking & tensioning.

Consult our specialists for calculations with our E-RappCalc© technical calculation program.

Our material, as well as the packaging, must be disposed of in a professional and environmentally friendly manner.