Technical datasheet

Peflex ESF 3/1 02+02 transparent M2 FG



Article code: SBPE589744

General information	
Product group	Synthetic Belts
Industry segment	General industry
Main product feature	Foodgrade
Indication of use	Rollers, Flat, Troughed, Slider bed

Belt construction		
Tension layer		polyester spun, flexible
Number of plies		1
Top side	material	Peflex, EVA
	finish	smooth, M2 Matt finish
	color	transparent
Bottom side	material	Peflex, EVA
	finish	matt, M2 Matt finish
	color	transparent

Characteristics		
Food Grade (FG)	yes	EC 1935/2004, EU 10/2011; FDA
Antistatic (AS)	no	
High conductive (HC)	no	
Flame-retardant (FR)	no	
ATEX approval	no	

Technical data						
Hardness	ISO 868	top side	90A	Shore		
Force at 1% elongation (static)	ISO 21181		3	N/mm	17.13	lbs/in.
Thickness	AB method KV.002	total	0.90	mm	0.04	in.
		top cover	0.20	mm	0.01	in.
Weight	AB method KV.004		1	kg/m²	0.2	lbs/ft²
Operating temperature	continuous	from / to	-20 / 50	°C	-4 / 122	°F
	short	from / to	-20 / 70	°C	-4 / 158	°F
Minimum pulley diameter	flexing		15	mm	0.59	in.
	backflexing		15	mm	0.59	in.
Manufacturing width	standard		3000	mm	118.11	in.
	maximum		3200	mm	125.98	in.

Fabrication

Hot splicing is always preferable. Glueing can only be done when the belt is exposed to normal temperature and the humidity is not excessive. For the working method, consult the splice information and the equipment literature. Apply the recommended splice as indicated in the seperate information.

Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

We recommend to keep the belt tension to a practical working minimum to maximize the service life of the belt and machine parts.

Always protect belts from sunlight/UV-radiation, avoid temperatures below 10°C and above 40°C, dust and dirt. Store belts in a cool and dry place and if possible in their original packaging.

For details consult 'Storage and handling instructions' or contact our specialist.

	nted data is subject to alteration. This data replaces that included in previous publications. Ammeraal Beltech excludes any liability for the al terms and conditions of sale and delivery, as applied by its operating companies, are all activities performed and services rendered by A	
© Ammeraal Beltech SB001 English A4	Modified: Friday, June 16, 2023, Printed: Thursday, October 26, 2023	Page:2 /