

# ZipGuide NR C37 natural + VG 22x14 PVC Green

Article code: ZLGR000006

## General information

<b>Product group</b>	ZipLink
<b>Industry segment</b>	Building materials; Bricks & tiles; Wood; Paper & print
<b>Main product feature</b>	High grip
<b>Application</b>	General conveying

## Belt construction

<b>Tension layer</b>		Ziplink fabric, stable
<b>Number of plies</b>		1
<b>Top side</b>	<b>material</b>	NR
	<b>finish</b>	profile, C37 Supergrip profile
	<b>color</b>	natural
<b>Bottom side</b>	<b>material</b>	PVC
	<b>finish</b>	ROPE, ROPE22X14GREEN
	<b>color</b>	green

## Characteristics

<b>Antistatic (AS)</b>	no
------------------------	----

## Technical data

<b>Hardness</b>	ISO 868	top side	40A Shore	
<b>Force at 1% elongation</b>	ISO 21181		10 N/mm	57.1 lbs/in.
<b>Thickness</b>	AB method KV.002		20.3 mm	0.8 in.
		top cover	5.3 mm	0.21 in.
<b>Weight</b>	AB method KV.004		20.81 kg/m <sup>2</sup>	4.26 lbs/ft <sup>2</sup>
<b>Operating temperature</b>	continuous	from / to	-40 / 121 °C	-40 / 249.8 °F
<b>Minimum pulley diameter</b>	flexing		120 mm	4.72 in.
	backflexing		225 mm	8.86 in.
<b>Manufacturing width</b>	standard		22 mm	0.87 in.
	maximum		22 mm	0.87 in.

## Fabrication

Ziplink belts can be endlessly, very easy and quick splicing without presses, fasteners or glues. Refer to the technical information for more information about splicing of Ziplink belts.

## Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

We recommend to keep the belt tension to a practical working minimum to maximize the service life of the belt and machine parts.

Always protect belts from sunlight/UV-radiation, avoid temperatures below 10°C and above 40°C, dust and dirt. Store belts in a cool and dry place and if possible in their original packaging.

For details consult 'Storage and handling instructions' or contact our specialist.