## Soliflex Sideskirt TPU/30 Capri blue FG MD

Article code: SFPU000680



General information	
Product group	Soliflex
Main product feature	Chemical resistant, Non-stick, Metal detectable

Belt construction	
Material	TPU
Top side	smooth
Bottom side	smooth
Color	Capri blue

Characteristics		
Food Grade (FG)	yes	EU 1935/2004, EU 10/2011; FDA; USDA

Technical data						
Hardness	ISO 868		85A	Shore		
Force at 1% elongation	ISO 21181		0.55	N/mm	3.14	lbs/in.
Belt thickness			3	mm	0.12	in.
Weight			3.3	kg/m²	0.68	lbs/ft²
Operating temperature	continuous	from / to	-20 / 60	°C	-4 / 140	°F
Minimum pulley diameter	flexing		30	mm	1.18	in.
	backflexing		30	mm	1.18	in.
Manufacturing width	maximum		750	mm	29.53	in.

Fabrication	
Recommended splice method	Butt weld

## **Additional information**

This sheet contains typical values, which apply to a temperature of approx. 20  $^{\circ}$ C (68  $^{\circ}$ F), unless otherwise stated, individual data may differ. Keep the belt tension to a practical working minimum for maximum belt and machine life.

Store loose and wrapped in plastic. The allowable product temperature may vary.



