Technical datasheet

SBR EF 17/2 00+C37 natural

Article code: LWSB560009



General information	
Product group	Light Weight Rubber
Industry segment	Airports; Logistics: Distribution & warehousing
Indication of use	Slider bed, Rollers, In/declined conveying

Belt construction		
Tension layer		RFL polyester, flexible
Number of plies		2
Top side	material	SBR, SB
	finish	profile, C37 Supergrip profile
	color	natural
Bottom side	material	fabric, polyester
	finish	impregnated
	color	red

Technical data						
Hardness	ISO 868	top side	45A	Shore		
Force at 1% elongation	ISO 21181		16	N/mm	91.36	lbs/in.
Thickness	AB method KV.002	belt	7.1	mm	0.28	in.
		top cover	3.8	mm	0.15	in.
Weight	AB method KV.004		5.9	kg/m²	1.21	lbs/ft²
Operating temperature	continuous	from / to	-40 / 121	°C	-40 / 249.8	°F
	short	from / to	-40 / 121	°C	-40 / 249.8	°F
Manufacturing width	standard		1829	mm	72.01	in.
	maximum		1829	mm	72.01	in.

Fabrication

Vulcanizing is always preferable. Cold splicing can only be done when the belt is exposed to normal temperature and the humidity is not excessive. For the working method, consult the splice information and the equipment literature. Apply the recommended splice as indicated in the separate information.

Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

We recommend to keep the belt tension to a practical working minimum to maximize the service life of the belt and machine parts.

Always protect belts from sunlight/UV-radiation, avoid temperatures below 10°C and above 40°C, dust and dirt. Store belts in a cool and dry place and if possible in their original packaging.

For details consult 'Storage and handling instructions' or contact our specialist.

acause of continuous dayalanmost, the acceptable	ad data is subject to alteration. This data confesse that include	ded in previous publications Ammoraal Palitant	n evoludes any liability for the incorrect use of the
pove stated information. Subject to the general Ammeraal Beltech LW001 English A4	ed data is subject to alteration. This data replaces that incluterms and conditions of sale and delivery, as applied by its of Modified: Thursday, March 2, 2023, Printed: Th		ed and services rendered by Ammeraal Beltech. Page:2