Technical datasheet

## AmSqueeze 314 A93-A93 2370x180x13.4mm



Article code: EWMS000240

General information	
Product group	endless woven
Industry segment	Food: Meat & poultry
Main product feature	Foodgrade, Abrasion resistant, Oil & grease resistant, Cut resistant
Application	Soft Separator
Indication of use	Special fine structured surface, Abrasive applications

Belt construction			
Tension layer		polyester	
Number of plies		1	
Top side	material	Ropanyl, TPU	
	finish	profile, A93-Rhombus	
	color	ivory	
Bottom side	material	Ropanyl, TPU	
	finish	profile, A93-Rhombus	
	color	white	

Characteristics		
Food Grade (FG)	yes	EC 1935/2004, EU 10-2011; FDA
Antistatic (AS)	no	
Flame-retardant (FR)	no	

Technical data						
Hardness	ISO 868	top side	76A	Shore		
		bottom side	85A	Shore		
Force at 1% elongation	ISO 21181		28	N/mm	159.88	lbs/in.
Thickness		total	13.4	mm	0.53	in.
		top cover	5.4	mm	0.21	in.
		bottom cover	5.4	mm	0.21	in.
Weight			21.8	kg/m²	4.46	lbs/ft²
Length		from / to	2370	mm		in.
Width		from / to	180	mm		in.
Operating temperature	continuous	from / to	-20 / 90	°C	-4 / 194	°F
	short	from / to	-30 / 110	°C	-22 / 230	°F
Minimum pulley diameter			134	mm	5.28	in.

Tolerances				
Length	± 1 %	minimum ±	20 mm	0.79 in.
Width		from / to	-1 / +1 mm	-0.04 / +0.04 in.
Thickness		±	0.2 mm	0.01 in.

## **Additional information**

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

Because of continuous development, the presented data is subject to alteration. This data replaces that included in previous publications. Ammeraal Beltech excludes any liability for the incorrect use of the above stated information. Subject to the general terms and conditions of sale and delivery, as applied by its operating companies, are all activities performed and services rendered by Ammeraal Beltech.