Endless Woven GK09XSB AmDough90XS Cotton 2.4mm



0.5 mm

Article code: RMFA000048

Alticic code: Ki-li A0000-to						
General information						
Product group	endless woven	endless woven				
Industry segment	Food: Bakery	Food: Bakery				
Main product feature	Foodgrade, Mois	Foodgrade, Moisture absorbant, Non-fraying				
Application	Rotary moulder	Rotary moulder belt, Rotary cutter, Oven infeed belt				
Indication of use	Knife edge trans	Knife edge transfer, Abrasive applications				
Belt construction						
Tension layer		broken t	will, cotton			
Number of plies		1				
Bottom side	material	material Ropanol, PUR				
	finish	impregn	ation			
		transpar	rent			
Characteristics						
Food Grade (FG)	yes	EC 1935	/2004, EU 10-2011; FDA			
Technical data						
Tensile Strength	ISO 21181			90 N/mm	513.91	lbs/in.
Thickness			total	2.4 mm	0.09	
Weight				1.5 kg/m ²	0.31	lbs/ft²
Length			min. / max.	800 / 52000 mm	31.5 / 2047.24	in.
Width			min. / max.	40 / 3400 mm	1.57 / 133.86	
Operating temperature	continuous		from / to	-10 / 90 °C	14 / 194	
	short		from / to	-30 / 110 °C	-22 / 230	
Minimum pulley diameter				4 mm	0.16	in.
Tolerances						
Length	± 2 %		minimum ±	20 mm	0.79	in.
Width	± 2 %		minimum ±	2 mm	0.08	in.

Thickness

0.02 in.

Process and Conveyor	Belt

Top view



Belttype	Material	Weave	Belt Thickness [mm]
AmDough 100	cotton	broken twill	2.8
AmDough 90	cotton	broken twill	2.4
AmDough 80	cotton / polyamide	broken twill	2.4
AmDough 70	cotton	plain	2.0
AmDough 60	cotton / polyamide	broken twill	2.4
AmDough 50	cotton / polyamide	plain	1.8
AmDough 40	cotton / polyamide	plain	2.0
AmDough 20	cotton / polyester	plain	2.0

There is a linear relationship between the AmDough absorption numbers:

Heavy dough: wet, high degree of moisture, AmDough belt with higher absorption factor

Light dough: dry, low degree of moisture, AmDough belt with lower absorption factor

Top side: always uncoated

Bottom side: PUR transparent food grade impregnation for stability, better wear resistance and longer belt life

Belt edges are reinforced with polyamide selvedges.

Dimension: length up to 100 m, width up to 3400 mm

Broken twill (GK) types are also available as Twill (k) versions.

Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

Diameter of knife edge <135° [mm]
5
4
4
3
4
3
3
3