

# Ultrasync F5 T10 Amtel Ivory NT

Article code: UCAM005310

## General information

<b>Product group</b>	Ultrasync
<b>Main product feature</b>	Positive drive, Wear resistant, Low friction tooth side

## Belt construction

<b>Tension layer</b>		Polyester fabric
<b>Number of plies</b>		1
<b>Top side</b>	<b>material</b>	Amtel, TPE-E
	<b>finish</b>	smooth
	<b>color</b>	ivory
<b>Bottom side</b>	<b>material</b>	Polyamide fabric, PA fabric
	<b>finish</b>	profile, T10
	<b>color</b>	green


## Characteristics

<b>Food Grade (FG)</b>	yes	ALL FOODSTUFF; ALL FOODSTUFF
<b>Oil &amp; Fat resistance</b>	yes	
<b>Antistatic (AS)</b>	no	

## Technical data

<b>Tooth</b>	profile		T10	
<b>Hardness</b>	ISO 868	top side	40D Shore	
<b>Belt tension at maximum allowable elongation</b>			5 N/mm	28.55 lbs/in.
<b>Thickness</b>		belt	4.5 mm	0.18 in.
		top cover	0.7 mm	0.03 in.
<b>Weight</b>			3.7 kg/m <sup>2</sup>	0.76 lbs/ft <sup>2</sup>
<b>Coefficient of friction</b>	tooth side against steel	dynamic	0,3	
		static	0,7	
<b>Operating temperature</b>	continuous	from / to	-20 / 110 °C	-4 / 230 °F
<b>Minimum pulley diameter</b>	flexing		49 mm	1.93 in.
	backflexing		70 mm	2.76 in.
<b>Belt width</b>	maximum		1000 mm	39.37 in.

## Reference images



## Fabrication

This information on the fabrication options is general, please contact Ammeraal Beltech to inquire for the specific fabrication possibilities of the belt of your choice.

Open end, prepared splice, spliced endless with mechanical fastener or a pin joint fastener.

Cleats welded or mechanically attached, metal teeth, guides welded or glued.

Covers can be welded, glued, coated or vulkanized onto the back side of the timing belt.

Thermoplastic covers can be embossed.

Perforations, lateral and longitudinal slots, lateral and longitudinal profiles.

## Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

The T10 tooth profile is according to ISO 17396.

Pulley load									
Number of teeth	outer Ø [mm]	Effective Ø [mm]	Ø with flanges [mm]	Max. bore [mm]	Number of teeth	outer Ø [mm]	Effective Ø [mm]	Ø with flanges [mm]	Max. bore [mm]
12	36.35	38.20	42	24	67	211.42	213.27	217	177
13	39.53	41.38	45	26	68	214.60	216.45	221	181
14	42.71	44.56	49	30	69	217.78	219.63	224	185
15	45.90	47.75	52	34	70	220.97	222.82	227	187
16	49.08	50.93	55	36	71	224.15	226.00	230	191
17	52.26	54.11	58	40	72	227.33	229.18	233	193
18	55.45	57.30	61	44	73	230.52	232.37	236	197
19	58.63	60.48	65	46	74	233.70	235.55	240	201
20	61.81	63.66	68	50	75	236.88	238.73	243	203
21	65.00	66.85	71	52	76	240.07	241.92	246	207
22	68.18	70.03	74	56	77	243.25	245.01	249	209
23	71.36	73.21	77	60	78	246.43	248.28	252	213
24	74.54	76.39	80	62	79	249.61	251.46	256	215
25	77.73	79.58	84	66	80	252.80	254.65	259	219
26	80.91	82.76	87	68	81	255.98	257.83	262	223
27	84.09	85.94	90	72	82	259.16	261.01	265	225
28	87.28	89.13	93	76	83	262.35	264.20	268	229
29	90.46	92.31	96	78	84	265.53	267.38	271	231
30	93.64	95.49	100	82	85	268.71	270.56	275	235
31	96.83	98.68	103	84	86	271.90	273.75	278	239
32	100.01	101.86	106	88	87	275.08	276.93	281	241
33	103.19	105.04	109	88	88	278.26	280.11	284	245
34	106.38	108.23	112	92	89	281.45	283.30	287	247
35	109.56	111.41	115	96	90	284.63	286.48	291	251
36	112.74	114.59	119	98	91	287.81	289.66	294	255
37	115.92	117.77	122	101	92	291.00	292.85	297	257
38	119.11	120.96	125	104	93	294.18	296.03	300	261
39	122.29	124.14	128	106	94	297.36	299.21	303	263
40	125.47	127.32	131	110	95	300.54	302.39	306	267
41	128.66	130.51	135	110	96	303.73	305.58	310	269
42	131.84	133.69	138	112	97	306.91	308.76	313	273
43	135.02	136.87	141	114	98	310.09	311.94	316	279
44	138.21	140.06	144	118	99	313.28	315.13	319	283
45	141.39	143.24	147	120	100	316.46	318.31	322	285
46	144.57	146.42	150	122	101	319.64	321.49	326	289
47	147.76	149.61	154	122	102	322.83	324.68	329	293
48	150.94	152.79	157	124	103	326.01	327.86	332	295
49	154.12	155.97	160	126	104	329.19	331.04	335	299

50	157.31	159.16	163	130	105	332.38	334.23	338	301
51	160.49	162.34	166	134	106	335.56	337.41	341	305
52	163.67	165.52	170	136	107	338.74	340.59	345	309
53	166.85	168.70	173	140	108	341.92	343.77	348	311
54	170.04	171.89	176	144	109	345.11	346.96	351	315
55	173.22	175.07	179	146	110	348.29	350.14	354	317
56	176.40	178.25	182	150	111	351.47	353.32	357	321
57	179.59	181.44	185	152	112	354.66	356.51	361	323
58	182.77	184.62	189	156	113	357.84	359.69	364	327
59	185.95	187.80	192	160	114	361.02	362.87	367	330
60	189.14	190.99	195	162	115	364.21	366.06	370	333
61	192.32	194.17	198	164	116	367.39	369.24	373	336
62	195.50	197.35	201	166	117	370.57	372.42	376	340
63	198.69	200.54	205	170	118	373.76	375.61	380	344
64	201.87	203.72	208	171	119	376.94	378.79	383	348
65	205.05	206.90	211	174	120	380.12	381.97	386	354
66	208.23	210.08	214	175					

**Standard**