

# AmSqueeze 320 A93-A93 2808x260x18mm

Article code: EWMS000383

## General information

<b>Product group</b>	endless woven
<b>Industry segment</b>	Food: Meat & poultry
<b>Main product feature</b>	Foodgrade, Abrasion resistant, Oil & grease resistant, Cut resistant
<b>Application</b>	Soft Separator

## Belt construction

<b>Tension layer</b>		polyester
<b>Number of plies</b>		1
<b>Top side</b>	<b>material</b>	Ropanyl, TPU
	<b>finish</b>	profile, A93-Rhombus
	<b>color</b>	ivory
<b>Bottom side</b>	<b>material</b>	Ropanyl, TPU
	<b>finish</b>	profile, A93-Rhombus
	<b>color</b>	white

## Characteristics

<b>Food Grade (FG)</b>	yes	EC 1935/2004, EU 10-2011; FDA
<b>Antistatic (AS)</b>	no	
<b>Flame-retardant (FR)</b>	no	

## Technical data

<b>Hardness</b>	ISO 868	top side	76A Shore	
		bottom side	85A Shore	
<b>Force at 1% elongation</b>	ISO 21181		28 N/mm	159.88 lbs/in.
<b>Thickness</b>		total	18 mm	0.71 in.
		top cover	7.7 mm	0.3 in.
		bottom cover	7.7 mm	0.3 in.
<b>Weight</b>			29.3 kg/m <sup>2</sup>	6 lbs/ft <sup>2</sup>
<b>Length</b>		from / to	2808 mm	in.
<b>Width</b>		from / to	260 mm	in.
<b>Operating temperature</b>	continuous	from / to	-20 / 90 °C	-4 / 194 °F
	short	from / to	-30 / 110 °C	-22 / 230 °F
<b>Minimum pulley diameter</b>			200 mm	7.87 in.

## Tolerances

<b>Length</b>	± 1 %	minimum ±	20 mm	0.79 in.
<b>Width</b>		from / to	-1 / +1 mm	-0.04 / +0.04 in.
<b>Thickness</b>		±	0.2 mm	0.01 in.