

# RU 367L050 + NES053 Black 98H x8.6

Article code: EBPU000113

## General information

<b>Product group</b>	Engineered belts, Pull down belts
<b>Industry segment</b>	Container & packaging; General industry
<b>Main product feature</b>	High grip, Non-marking, Wear resistant

## Belt specifics

<b>Previous AB Item number</b>	x-TNA TIMING
--------------------------------	--------------

## Belt construction

<b>Base belt or substrate</b>	<b>type</b>	Timing belt	
	<b>pitch type</b>	L	
	<b>tensionmember</b>	glass fiber	
<b>Belt cover</b>	<b>material</b>	Neoprene rubber	
	<b>hardness</b>	55A	Shore
	<b>color</b>	black	

## Characteristics

<b>Foodgrade (FG)</b>	<b>cover material</b>	no	
<b>Oil &amp; fat resistant</b>		yes	good

## Technical data

<b>Belt</b>	<b>thickness</b>		8.6 mm	0.34 in.
	<b>length</b>		932.18 mm	36.7 in.
	<b>width</b>		12.7 mm	0.5 in.
<b>Coefficient of friction</b>	<b>tooth side to steel</b>	dynamic	0,3	
<b>Operating temperature</b>	<b>continuous</b>	from / to	-5 / 70 °C	23 / 158 °F
<b>Minimum pulley diameter</b>	<b>flexing</b>		45 mm	1.77 in.
	<b>backflexing</b>		not advised	

## General information



## Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.