

AmSqueeze 515 A93-A93 2840x260x15mm

Article code: EWMS000212

General information

Product group	endless woven
Industry segment	Food: Meat & poultry
Main product feature	Foodgrade, Abrasion resistant, Oil & grease resistant, Cut resistant
Application	Soft Separator
Indication of use	Special fine structured surface, Abrasive applications

Belt construction

Tension layer		polyester
Number of plies		1
Top side	material	Ropanyl, TPU
	finish	profile, A93-Rhombus
	color	white
Bottom side	material	Ropanyl, TPU
	finish	profile, A93-Rhombus
	color	white

Characteristics

Food Grade (FG)	yes	EC 1935/2004, EU 10-2011; FDA
Antistatic (AS)	no	
Flame-retardant (FR)	no	

Technical data

Hardness	ISO 868	top side	85A Shore	
		bottom side	85A Shore	
Force at 1% elongation	ISO 21181		28 N/mm	159.88 lbs/in.
Thickness		total	15 mm	0.59 in.
		top cover	6.2 mm	0.24 in.
		bottom cover	6.2 mm	0.24 in.
Weight			24.4 kg/m ²	5 lbs/ft ²
Length		from / to	2840 mm	in.
Width		from / to	260 mm	in.
Operating temperature	continuous	from / to	-20 / 90 °C	-4 / 194 °F
	short	from / to	-30 / 110 °C	-22 / 230 °F
Minimum pulley diameter			150 mm	5.91 in.

Tolerances

Length	± 1 %	minimum ±	20 mm	0.79 in.
Width		from / to	-1 / +1 mm	-0.04 / +0.04 in.
Thickness		±	0.2 mm	0.01 in.

Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.