General information

Fabric EZP 8/1 0+0 white

Article code: ZLFA000001



Product group	Ziplink		
Belt construction			
Tension layer		Ziplink fabric, flexible	
Number of plies		1	
Top side	material	fabric, polyester	
	finish	bare fabric	
	color	white	
Bottom side	material	fabric, polyester	
	finish	bare fabric	
	color	white	

Characteristics		
Food Grade (FG)	yes	FDA

Technical data				
Force at 1% elongation	ISO 21181		8 N/mm	45.68 lbs/in.
Thickness	AB method KV.002		2.6 mm	0.1 in.
		top cover	0 mm	0 in.
Weight	AB method KV.004		1.39 kg/m ²	0.28 lbs/ft ²
Manufacturing width	standard		1829 mm	72.01 in.
	maximum		1829 mm	72.01 in.

Fabrication

Ziplink belts can be endlessed, very easy and quick splicing without presses, fasteners or glues. Refer to the technical information for more information about splicing of Ziplink belts.

Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

We recommend to keep the belt tension to a practical working minimum to maximize the service life of the belt and machine parts.

Always protect belts from sunlight/UV-radiation, avoid temperatures below 10°C and above 40°C, dust and dirt. Store belts in a cool and dry place and if possible in their original packaging.

For details consult 'Storage and handling instructions' or contact our specialist.

Because of continuous development, the presented data is subject to alteration. This data above stated information. Subject to the general terms and conditions of sale and delivery	replaces that included in previous publication y, as applied by its operating companies, are	ns. Ammeraal Beltech excludes any liability all activities performed and services render	for the incorrect use of the ed by Ammeraal Beltech.