

UU N22 RFQ FG

Article code: FBUE054535

General information

Product group	High performance flat belts
Product sub type	QuickSplice
Industry segment	Food, Logistics; Paper & print
Main product feature	Elastic, Foodgrade
Application	General conveying, Mail handling, Paper processing, Printing & finishing
Indication of use	Bi-directional

Belt construction

Tension member		Polyurethane
Top side	material	Polyurethane
	finish	Fine
	color	Royal blue
Bottom / Pulley side	material	Polyurethane
	finish	Rough
	color	black

Characteristics

Food Grade (FG)	yes	EC 1935/2004, EU 10/2011; FDA
Antistatic (AS)	yes	ISO 284
High conductive (HC)	yes	ISO 284 (bottom side only)
ATEX approval	no	

Technical data

Belt thickness	ISO 2286-3		1.85 mm	0.07 in.
	tolerance +/-		0.1 mm	0 in.
Weight	ISO 290703-1		2.25 kg/m ²	0.46 lbs/ft ²
Force at 6% elongation	ISO 21181	dynamic	2.2 N/mm	12.56 lbs/in.
	ISO 527	static	2.95 N/mm	16.84 lbs/in.
Recommended elongation		min. / max.	0.5 / 6 %	
Coefficient of friction, dynamic	ISO 21182	bottom side to steel	0,2 μ	
		top side to steel	0,2 μ	
Minimum pulley diameter	flexing		25 mm	0.98 in.
	back flexing		25 mm	0.98 in.
Operating temperature	continuous	from / to	-10 / 60 °C	14 / 140 °F
Belt width	standard		1200 mm	47.24 in.

Fabrication

Recommended splice method	QuickSplice30
Alternative splice method	OverLapSplice3

Additional Information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

Consult our specialists for further instructions regarding joining, storage & maintenance, tracking & tensioning.

Consult our specialists for calculations with our E-RappCalc© technical calculation program.

Our material, as well as the packaging, must be disposed of in a professional and environmentally friendly manner.