

Fabric EZP 8/1 0+0 yellow

Article code: ZLFA000003

General information

Product group Ziplink

Belt construction

Tension layer		Ziplink fabric, flexible
Number of plies		1
Top side	material	fabric, polyester
	finish	bare fabric
	color	yellow
Bottom side	material	fabric, polyester
	finish	bare fabric
	color	yellow

Characteristics

Food Grade (FG) yes FDA

Technical data

Force at 1% elongation	ISO 21181	8 N/mm	45.68 lbs/in.
Thickness	AB method KV.002	2.6 mm	0.1 in.
Weight	AB method KV.004	1.39 kg/m ²	0.28 lbs/ft ²
Manufacturing width	standard	1829 mm	72.01 in.
	maximum	1829 mm	72.01 in.

Fabrication

Ziplink belts can be endlessed, very easy and quick splicing without presses, fasteners or glues. Refer to the technical information for more information about splicing of Ziplink belts.

Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

We recommend to keep the belt tension to a practical working minimum to maximize the service life of the belt and machine parts.

Always protect belts from sunlight/UV-radiation, avoid temperatures below 10°C and above 40°C, dust and dirt. Store belts in a cool and dry place and if possible in their original packaging.

For details consult 'Storage and handling instructions' or contact our specialist.

Because of continuous development, the presented data is subject to alteration. This data replaces that included in previous publications. Ammeraal Beltech excludes any liability for the incorrect use of the above stated information. Subject to the general terms and conditions of sale and delivery, as applied by its operating companies, are all activities performed and services rendered by Ammeraal Beltech.