**General information** 

Characteristics

## Soliflex TPU/70 M1T I. blue FG

Article code: SFPU000968



Donato de la companya	C. J. S
Product group	Soliflex
Belt construction	
Material	TPU
Top side	M1 Fine matt finish, M1 Fine matt finish
Bottom side	M1 Fine matt finish, M1 Fine matt finish
Color	Light blue

Tochnical data	Food Grade (FG)	yes	EU 1935/2004, EU 10/2011; FDA; USDA
recinical data	Technical data	•	

Technical data						
Hardness	ISO 868		53D	Shore		
Force at 1% elongation	ISO 21181		4	N/mm	22.84	lbs/in.
Belt thickness			7	mm	0.28	in.
Weight			8.5	kg/m²	1.74	lbs/ft²
Operating temperature	continuous	from / to	-5 / 70	°C	23 / 158	°F
Minimum pulley diameter	flexing		na	mm		in.
	backflexing		na	mm		in.
Manufacturing width	maximum		1371.6	mm	54	in.
	standard		1371.6	mm	54	in.

Fabrication	
Recommended splice method	Butt weld

## **Additional information**

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ. Keep the belt tension to a practical working minimum for maximum belt and machine life.

Store loose and wrapped in plastic. The allowable product temperature may vary.