

PVC ESF 15/3 01+10 white FG

Article code: SBAS040084

General information

Product group	Synthetic Belts
Main product feature	Foodgrade
Indication of use	Flat, Rollers, Troughed, Slider bed

Belt construction

Tension layer		polyester, flexible
Number of plies		3
Top side	material	PVC, PVC
	finish	smooth, glossy
	color	white
Bottom side	material	PVC, PVC
	color	white

Characteristics

Food Grade (FG)	yes	
Antistatic (AS)	no	
High conductive (HC)	no	
Flame-retardant (FR)	no	
ATEX approval	no	

Technical data

Force at 1% elongation (static)	ISO 21181		15 N/mm	85.65 lbs/in.
Thickness	AB method KV.002	total	3.5 mm	0.14 in.
		top cover	1 mm	0.04 in.
Weight	AB method KV.004		4.1 kg/m ²	0.84 lbs/ft ²
Operating temperature	continuous	from / to	-12 / 82 °C	10.4 / 179.6 °F
	short	from / to	-12 / 100 °C	10.4 / 212 °F
	backflexing		76.2 mm	3 in.
Manufacturing width	standard		1828.8 mm	72 in.
	maximum		1828.8 mm	72 in.

Fabrication

Hot splicing is always preferable. Glueing can only be done when the belt is exposed to normal temperature and the humidity is not excessive. For the working method, consult the splice information and the equipment literature. Apply the recommended splice as indicated in the separate information.

Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

We recommend to keep the belt tension to a practical working minimum to maximize the service life of the belt and machine parts.

Always protect belts from sunlight/UV-radiation, avoid temperatures below 10°C and above 40°C, dust and dirt. Store belts in a cool and dry place and if possible in their original packaging.

For details consult 'Storage and handling instructions' or contact our specialist.

Because of continuous development, the presented data is subject to alteration. This data replaces that included in previous publications. Ammeraal Beltech excludes any liability for the incorrect use of the above stated information. Subject to the general terms and conditions of sale and delivery, as applied by its operating companies, are all activities performed and services rendered by Ammeraal Beltech.