**Technical datasheet** 

Canaval information

## Excon EF 24/3 06+10 White AS FG /600

Am

Ammeraal Beltech
Innovation & Service in Belting

Article code: SBMD000207

deneral into mation				
Product group	Synthetic Belts			
Belt construction				
Number of plies		3		
Top side	material	Excon, Excon		
	finish	profile		
	color	white		
Bottom side	material	Excon		
	finish	smooth		
	color	white		

Technical data					
Manufacturing width	standard	600	mm 23.62	in.	
	maximum	600	mm 23.62	in.	

## **Fabrication**

Hot splicing is always preferable. Glueing can only be done when the belt is exposed to normal temperature and the humidity is not excessive. For the working method, consult the splice information and the equipment literature. Apply the recommended splice as indicated in the seperate information.

## **Additional information**

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ. We recommend to keep the belt tension to a practical working minimum to maximize the service life of the belt and machine parts.

Always protect belts from sunlight/UV-radiation, avoid temperatures below 10°C and above 40°C, dust and dirt. Store belts in a cool and dry place and if possible in their original packaging.

For details consult 'Storage and handling instructions' or contact our specialist.