

# Solicord V-belt TPE 55D Blue SM FG 22x14

Article code: SCVB000026

## General information

<b>Product group</b>	SoliCord
----------------------	----------

## Construction

<b>Material</b>	TPE
<b>(Top)surface finish</b>	smooth
<b>Color</b>	blue
<b>Shape</b>	Vee
<b>Execution</b>	solid

## Characteristics

<b>Food Grade (FG)</b>	yes	all foodstuff; all foodstuff
<b>Antistatic (AS)</b>	no	
<b>ATEX approval</b>	no	

## Technical data

<b>Hardness</b>	ISO 868		55D Shore	
<b>Recommended pre-tension</b>			3 %	
<b>Working tension</b>			50 daN/cm <sup>2</sup>	
<b>Diameter</b>			0 mm	0 in.
<b>Cross section</b>			2.4 cm <sup>2</sup>	
<b>Weight</b>			0.29 kg/m	0.06 lb/ft
<b>Operating temperature</b>	continuous	from / to	-30 / 100 °C	-22 / 212 °F
<b>Minimum pulley diameter</b>			230 mm	9.06 in.
<b>Coefficient of friction</b>	against steel	dynamic	0,35	
	against PE		0,15	
	against HDPE		0,1	
<b>Manufacturing length</b>	maximum		50000 mm	1968.5 in.

## Fabrication

<b>Recommended splice types</b>	Butt weld
<b>Splice equipment</b>	Only use equipment supplied or approved by Ammeraal Beltech.
<b>Splicing on site</b>	Always first make a test splice to confirm the right settings and proper pre-heating of the equipment.

## Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

Keep the belt tension to a practical working minimum for maximum belt and machine life.

Always protect belts from sunlight/UV-radiation, avoid temperatures below 10°C and above 40°C, dust and dirt.