

Excon EF 24/3 R22+10 M1 AS FG

Article code: SBMD000262

General information

Product group	Synthetic Belts
Industry segment	Food
Main product feature	Antistatic, Foodgrade, Oil & grease resistant
Indication of use	Flat, Rollers, Troughed

Belt construction

Tension layer		polyester, flexible
Number of plies		3
Top side	material	PVC, PVC
	finish	smooth, M1 Fine matt finish
	color	Dark blue
Bottom side	material	Excon, PVC
	finish	M1 Fine matt finish, R22 fine square pyramid
	color	Dark blue

Characteristics

Food Grade (FG)	yes	Yes; Yes
Antistatic (AS)	yes	
Flame-retardant	no	
ATEX approval	no	

Technical data

Hardness	ISO 868	top side	72A Shore	
Force at 1% elongation (static)	ISO 21181		24 N/mm	137.04 lbs/in.
Thickness	AB method KV.002	total	5.5 mm	0.22 in.
		top cover	1 mm	0.04 in.
Weight	AB method KV.004		6.9 kg/m ²	1.41 lbs/ft ²
Operating temperature	continuous	from / to	-10 / 70 °C	14 / 158 °F
Minimum pulley diameter	flexing		180 mm	7.09 in.
	backflexing		230 mm	9.06 in.
Manufacturing width	standard		2400 mm	94.49 in.
	maximum		2400 mm	94.49 in.

Fabrication

Hot splicing is always preferable. Glueing can only be done when the belt is exposed to normal temperature and the humidity is not excessive. For the working method, consult the splice information and the equipment literature. Apply the recommended splice as indicated in the separate information.

Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ. We recommend to keep the belt tension to a practical working minimum to maximize the service life of the belt and machine parts. Always protect belts from sunlight/UV-radiation, avoid temperatures below 10°C and above 40°C, dust and dirt. Store belts in a cool and dry place and if possible in their original packaging. For details consult 'Storage and handling instructions' or contact our specialist.