General information

Soliflex TPU/40 M1T light blue FG

Article code: SFPU000951



Product group	Soliflex	
Belt construction		
Material	TPU	
Top side	M1 Fine matt finish, M1 Fine matt finish	
Bottom side	Matt, M1 Fine matt finish	
Color	Light blue	

Characteristics			
Food Grade (FG)	yes	EU 1935/2004, EU 10/2011; FDA; USDA	

Technical data						
Hardness	ISO 868		53D	Shore		
Force at 1% elongation	ISO 21181		3.5	N/mm	19.99	lbs/in.
Belt thickness			4	mm	0.16	in.
Weight			4.8	kg/m²	0.98	lbs/ft²
Operating temperature	continuous	from / to	-5 / 70	°C	23 / 158	°F
Minimum pulley diameter	flexing		130	mm	5.12	in.
	backflexing		130	mm	5.12	in.
Manufacturing width	maximum		1376.1	mm	54.18	in.
	standard		1371.6	mm	54	in.

Fabrication	
Recommended splice method	Butt weld

Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ. Keep the belt tension to a practical working minimum for maximum belt and machine life.

Store loose and wrapped in plastic. The allowable product temperature may vary.